



## AT-FS708LE

### Unmanaged Fast Ethernet Switch, Featuring Low Power Technology

#### AT-FS708LE-xx

8 port 10/100TX low power unmanaged 'Green' switch with external power supply

#### ECO-Friendly

The AT-FS708LE eco friendly switch conforms with Allied Telesis' commitment to environmentally friendly processes and products. It is designed to minimize power consumption through the use of a high efficiency power supply and a low power chipset.

With a low 2.0W typical power consumption\*, an EnergyStar rated power supply, and a reduction in power during after-work hours (overnight mode) – as well as other power saving features included as standard, the Allied Telesis AT-FS708LE truly lives up to it's name as an 'eco friendly' switch.

Not only does this help the planet by reducing the carbon footprint of each switch, it also lowers the Total Cost of Ownership (TCO) to the user, as the product costs less to run, and has improved reliability.

With all of these power saving features, the new eco friendly AT-FS708LE saves the user up to 59% in power consumption over our previous version (see power saving table).

#### High Performance

Providing powerful 10/100 switching solutions for desktop and small network environments, the Allied Telesis FS700 series of unmanaged switches features full auto-negotiating 10/100 ports. These ports enable the switches to detect the speed and duplex modes of attached devices, enabling them to automatically configure for the best possible performance.

#### Flexibility

Available as 5, 8, 16, or 24 port models, the FS700 series meets a multitude of power requirements with both internal and external power-supply options. Also, wall desk, and rackmounting options give users ultimate flexibility in selecting the model that meets their physical deployment requirements.

#### Simplified Installation

Fully auto-configuring FS700 series switches require minimal set-up by the user. Auto-sensing ports enable seamless and simple connectivity between existing 10Mbps Ethernet and 100Mbps Fast Ethernet UTP devices—and all units can be installed in minutes. Every FS700 series model is equipped with MDI/MDI-X ports for simple connection to other hubs and switches. Finally, easy to read front panel LEDs show ongoing switch status and simplify troubleshooting.

#### Quality and Reliability


Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesis offers proven reliability and industry recognized quality.

#### Key Features

- 8 10/100TX ports
- Wirespeed technology
- Non-blocking architecture
- Auto-negotiation ports
- Auto MDI/MDI-X ports
- Transparent to VLAN packets
- Half and full-duplex flow control
- External power supply
- Sturdy metal case

#### Power-saving Features

- Maximum switch power consumption - 2.5W
- Typical switch power consumption\* - 2.0W
- External, EnergyStar rated power supply
- Overnight mode - when PCs are powered off, the switch reduces power
- Power down mode
- Measure and minimize - checks the lengths of the cable and sends only enough power for specific cable length



Powered by an ENERGY STAR® qualified adapter for a better environment

\* 6 ports connected with 3m cables.

# AT-FS708LE | Unmanaged Fast Ethernet Switches, Low Power Technology

## Performance

14,800pps for 10Mbps Ethernet  
148,000pps for 100Mbps Fast Ethernet

Throughput 1.19Mpps  
Switching capacity 1.6Gbps

MAC addresses Up to 4K

Packet buffer 256K

## Interface Connections

10/100TX RJ-45

Half/full-duplex  
Auto-negotiation  
Auto MDI/MDI-X on all ports

## Power Characteristics

Frequency 50 to 60Hz  
7.5vDC, 1A

EnergyStar compliant external power adapter

## Environmental Specifications

Operating temp. 0°C to 40°C (32°F to 104°F)  
Non-operating temp. -25°C to 70°C (-13°F to 158°F)  
Operating humidity 5% to 80% non-condensing  
Storage humidity 5% to 95% non-condensing

## Power Saving % Chart

Ports	Status	Non-green vs Green Power Saving %			
		3m cable		100m cable	
		AC side	DC side	AC side	DC side
Overnight mode		59.2%	16.1%	59.9%	19.9%
8 port	Only link, no traffic	34.6%	26.2%	25.8%	15.6%
	Smartbit, 100% utilization TX	34.1%	25.6%	25.2%	18.7%
7 port	Only link, no traffic	35.3%	26.7%	26.4%	16.8%
	Smartbit, 100% utilization TX	35.3%	25.4%	26.7%	16.6%
6 port	Only link, no traffic	36.6%	28.2%	27.5%	17.6%
	Smartbit, 100% utilization TX	36.5%	26.9%	27.3%	16.8%
5 port	Only link, no traffic	37.3%	27.5%	29.2%	18.3%
	Smartbit, 100% utilization TX	37.9%	28.8%	30.2%	20.6%
4 port	Only link, no traffic	40.3%	28.5%	33.4%	21.2%
	Smartbit, 100% utilization TX	39.5%	30.1%	32.9%	23.8%
3 port	Only link, no traffic	41.9%	29.9%	36.5%	23.3%
	Smartbit, 100% utilization TX	43.4%	31.4%	37.7%	26.9%
2 port	Only link, no traffic	46.4%	30.8%	41.9%	26.6%
	Smartbit, 100% utilization TX	46.5%	34.7%	41.9%	29.3%

## Technical Specifications

### Physical Characteristics

Dimensions 13cm x 7cm x 2.5cm  
(W x D x H) (5.12" x 2.77" x 1.0")  
Weight 0.266kgs (0.60lbs)

### Wall-mount or Desktop

Units come with wall-mount brackets

### Standards and Compliance

IEEE 802.3 10T Ethernet  
IEEE 802.3u 100TX Fast Ethernet  
IEEE 802.3x Flow control

### Electrical/Mechanical Approvals

UL 1950  
CSA 22.2 No. 950  
FCC/EN55022 Class B  
VCCI Class B  
EN60950 (TUV)  
EN55024  
CE

## Ordering Information

AT-FS708LE-xx  
8 port 10/100TX low power unmanaged switch with external power supply

Where xx = 10 for US power adapter  
20 for no power adapter  
30 for UK power adapter  
40 for Australian power adapter  
50 for European power adapter

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

[www.alliedtelesis.com](http://www.alliedtelesis.com)

© 2009 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000309 Rev. B